

# **BII** **ALUMINUM TWO PIECE VERMIN PROOF WELL CAP**

- Furnished with stainless hardware
- Easy to install
- O-ring system ensures reliable watertight seal between well casing and retainer ring
- Seal between cover & retainer ring made with a second O-ring compression seal
- Easy access for maintenance
- Greater clearance for submersible pump cable
- Grounding terminal provided
- Durable finish
- Painted finish also available
- 4" and 5" will be available in the future



PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	QUANTITY	
	I.D.	O.D.			CTN	CASE
<b>Aluminum</b>						
WTC-A06	6"	6 5/8"	1" FPT	(2) 3/4"	1	6
<b>Painted Blue</b>						
WTC-A06-BLUE	6"	6 5/8"	1" FPT	(2) 3/4"	1	6

Many Products . . . One Source . . . Boshart



25 Whaley Ave., P.O. Box 310  
 Milverton, ON, Canada N0K 1M0  
 Tel: 1-519-595-4444  
 Toll Free: 1-800-561-3164  
 Fax: 1-519-595-4380  
 web: www.boshart.com



# DELUXE 6" CAST IRON WATERTIGHT WELL CAP

- Furnished with stainless hardware
- Easy to install
- O-ring system ensures reliable watertight seal between well casing and retainer ring
- Seal between cover & retainer ring made with a second O-ring compression seal
- Easy access for maintenance
- Greater clearance for submersible pump cable
- Grounding terminal provided
- Durable finish



Part No.	Casing Size (In.)		Conduit Connection	Air Vents	Shipping Wgt-lbs.	Quantity	
	I.D.	O.D.				Ctn	Case
WTC-C06	6"	6 5/8"	1" FPT	(2) 3/4"	9.5	1	6
WTC-C06-12	6"	6 5/8"	1 1/4" FPT	(2) 3/4"	9.5	1	6



25 Whaley Ave., P.O. Box 310  
Milverton, ON, Canada N0K 1M0  
Tel: 1-519-595-4444  
Toll Free: 1-800-561-3164  
Fax: 1-519-595-4380  
web: www.boshart.com

# **BII** **6" PLASTIC TWO PIECE WELL CAP - GLUE ON STYLE**

---

- Furnished with stainless hardware
- Easy to install
- Seal between cover & retainer ring made with a second O-ring compression seal
- Easy access for maintenance
- Greater clearance for submersible pump cable
- Glue on style for PVC casing
- Interchangeable with WTC-A06, tops and bottoms



WTC-G-P0625 (Glue on style for PVC casing)

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	QUANTITY	
	I.D.	O.D.			CTN	CASE
WTC-G-P0625	6 1/4"	6.900"	1" FPT	(2) 3/4"	1	6

Many Products . . . One Source . . . Boshart



25 Whaley Ave., P.O. Box 310  
 Milverton, ON, Canada N0K 1M0  
 Tel: 1-519-595-4444  
 Toll Free: 1-800-561-3164  
 Fax: 1-519-595-4380  
 web: [www.boshart.com](http://www.boshart.com)

# ALUMINUM WATERTITE LOCKING WELL CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- Second O-ring used to seal cover and retainer ring
- Locking feature to ensure a secure/tamper-proof access
- Grounding terminal and bolt provided
- A well log is provided inside each cap to record installation data/specifications



6" Well Cap -  
Set Screw Design

A positive compression seal is achieved by tightening a single set screw on a specially designed tapered surface ensuring a positive seal. **PATENT PENDING**



8"-10"-12" Well Caps  
6-Bolt Design

A positive compression seal is achieved by tightening six bolts.



PART NO.	CASING SIZE (IN.)		CONDUIT PIPE	AIR VENTS	WGT PER UNIT-lbs	QTY CASE
	I.D.	O.D.				
WTMLC-A06	6	6-5/8	1" FPT	(2) 3/4"	4.0	12
WTCL-A08	8	8-5/8	1-1/4" FPT	(2) 3/4"	5.5	6
WTCL-A10	10	10-5/8	1-1/4" FPT	(2) 3/4"	6.0	6
WTCL-A12	12	12-3/4	1-1/4" FPT	(2) 3/4"	6.5	6

Many Products . . . One Source . . . Boshart



25 Whaley Ave., P.O. Box 310  
 Milverton, ON, Canada N0K 1M0  
 Tel: 1-519-595-4444  
 Toll Free: 1-800-561-3164  
 Fax: 1-519-595-4380  
 web: www.boshart.com

# ALUMINUM COVER WITH GLUE-ON ABS RING WATERTITE LOCKING WELL CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening a single set screw on a specially designed tapered surface ensuring a positive seal
- Locking feature provides a secure/tamper-proof installation
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications



Glue on style for PVC casing



PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT-lbs	QTY CASE
	I.D.	O.D.				
WTMLC-G-AP04	4"	4.500"	1" FPT	(2) 3/4"	2.03	20
WTMLC-G-AP045	4-1/2"	4.950"	1" FPT	(2) 3/4"	2.18	16
WTMLC-G-AP05	5"	5.563"	1" FPT	(2) 3/4"	2.36	16
WTMLC-G-AP0625	6-1/4"	6.900"	1" FPT	(2) 3/4"	2.40	12

Many Products . . . One Source



25 Whaley Ave., P.O. Box 310  
 Milverton, ON, Canada N0K 1M0  
 Tel: 1-519-595-4444  
 Toll Free: 1-800-561-3164  
 Fax: 1-519-595-4380  
 web: www.boshart.com